

**Spannungseinsatzbereich, Baureihe ILI**

**Range of operating voltage, type ILI**

**Intervalle de mises sous tension, version ILI**

**Rango de ajuste de tensión, variante de serie ILI**

**Campo di applicazione della tensione, serie ILI**

**Drehstrommotor 3~400V/690V (keine UL-Zulassung)**

**Three phase alternating current motor 3~400V/690V (no UL-certification)**

**Moteur à courant triphasé 3~400V/690V (pas d'homologation UL)**

**Motor trifásico 3~400V/690V (sin aprobación UL)**

**Motore a corrente trifase 3~400V/690V (nessun approvazione UL)**

Betriebsart Mode Couplage Modo de funcionamiento Modalità operativa	Bg Frame size HA Tamaño mod.	Lüfterdurchmesser Blower diameter Diamètre des ventateurs Diametro del ventilatore Diametro del ventilatore	Spannungsbereich Range of voltage Plage de tension Rango de tensiones Campo di tensione		Max. zulässiger Strom Max. permissible current Courant max. admissible Corrente máxima permitida Corrente massima consentita	max. Leistungsaufnahme max. power input max. puissance absorbée Consumo máxima de energía Potenza massima assorbita		
		(mm)	50Hz (V)	60Hz	50Hz (A)	60Hz	50Hz (W)	60Hz
3~Y	200-249 ILI	375	346-690	380-690	0.53	0.36	238	247
	250-450 ILI	470	346-690	380-690	0.84	0.72	360	478
3~Δ	200-249 ILI	375	200-400	220-400	0.91	0.62	238	247
	250-450 ILI	470	200-400	220-400	1.45	1.25	360	478

mit b-seitigem Referenzlagerschild /with bearing shield of reference on side b /avec de référence flasque latérale b /  
placa de referencia en el lado b /con targhetta cuscinetti di riferimento lato b