

Volumenstrom [m³/h], Baureihe ILI
Air current capacity [m³/h], type ILI
Courant en volumes [m³/h], version ILI
Caudal volumétrico [m³/h], variante de serie ILI
Portata in volume[m³/h], serie ILI

Bg Frame size HA Tamaño mod.	400V 50Hz	460V 60Hz	400V 50Hz	460V 60Hz	400V 50Hz	400V 60Hz
	3 ~ Y 2-polig	3 ~ Y 2-polig	3 ~ Y 4-polig	3 ~ Y 4-polig	3 ~ Δ 4-polig	3 ~ Δ 4-polig
63	54	69	/	/	/	/
71	78	99	/	/	/	/
80	128	151	/	/	/	/
90	216	258	109	130	/	/
100	278	328	141	164	/	/
112	355	418	180	210	/	/
132	550	650	290	340	/	/
160	980	1160	520	620	/	/
180	1200	1379	619	695	/	/
200	1324	1575	656	776	/	/
204	/	/	1062	1237	1103	1313
225	/	/	1283	1467	1337	1580
249	/	/	1457	1714	1532	1832
250	/	/	1672	1919	1764	2097
280	/	/	2170	2472	2319	2760
315	/	/	2560	2935	2747	3274
355	/	/	4069	4665	4263	5022
400	/	/	5166	5922	5355	6245
450	/	/	6351	7444	6583	7850
500	/	/	8072	9254	8367	9758
560	/	/	9688	11216	10042	11827

mit b-seitigem Referenzlagerschild /with bearing shield of reference on side b /avec de référence flasque
 latérale b / placa de referencia en el lado b /con targhetta cuscinetti di riferimento lato b