

Spannungseinsatzbereich, Baureihe ILI
Range of operating voltage, type ILI
Intervalle de mises sous tension, version ILI
Rango de ajuste de tensión, variante de serie ILI
Campo di applicazione della tensione, serie ILI

Gleichstrommotor 24V DC (G31)
 Direct current motor 24V DC (G31)
 Moteur à courant continu 24V DC (G31)
 Motor de corriente continua 24V DC (G31)
 Motore a corrente continua 24V DC (G31)

Bg	Frame size	HA	Tamaño mod.	Lüfterdurchmesser	Blower diameter	Diamètre des ventilateurs	Diametro del ventilatore	Diametro del ventilatore	Spannungsbereich	Range of voltage	Plage de tension	Rango de tensiones	Campo di tensione	Max. zulässiger Strom	Max. permissible current	Courant max. admissible	Corriente máxima permitida	Corrente massima consentita	max. Leistungsaufnahme	max. power input	max. puissance absorbée	Consumo máxima de energía	Potenza massima assorbita
				(mm)					(V)					(A)					(W)				
	63			118					24					0,32					7,70				
	71			132					24					0,42					10,00				
	80			150					24					0,59					14,10				
	90			169					24					0,82					19,80				
	100			187					24					1,16					27,80				
	112			210					24					1,64					39,40				

mit b-seitigem Referenzlagerschild /with bearing shield of reference on side b /avec de référence flasque latérale b / placa de referencia en el lado b /con targhetta cuscinetti di riferimento lato b